

Ref. Code: AP058

Date: April 2016



Dry Fix Ridge System

Product Features

A mortar-free, mechanically fixed ridge. Easier, quicker and safer to install than a mortared ridge. The URS6 provides continuous ventilation through the ridge roll, which sits above the tiles and below the ridge cap. Ventilation provided is over 100cm²/m, so it more than achieves BS5250 (50cm²/m).

- Quick and easy to install
- Fire resistant to SAB to BS476 part 3 and Class 3 to BS476 part 7
- Ventilation to BS5250 (equivalent to 5mm free ventilation area either side of the ridge.)
- Accommodates more ridge tiles than any other system

The URS6 Consists of:

- 6M Dry Ridge Roll Out Tray
- 13 Dry Ridge Union Strips
- 13 Dry Ridge Caps
- 13 Dry Ridge Brackets

Product Requirements	URS6
Statutory Requirements	To provide ventilation in accordance with Building Regs Document C2, BS5250:2011 and Building Standards (Scotland) Regulations
Functional Requirements	To protect the ridge of the roof, and provide continuous ventilation along the ridge.

Product Specification	
Code	URS6/B
Length	Roll Out Tray is 6M long.
Width	System designed for standard ridge tiles 450mm width.
Standard Weight	3.1Kg
Colour	Black