

Ref. Code: AP029

Date: April 2016



HP1, HP2 Economy Slate Vent


Product Description

Corovent Economy Slate Vents provide low or high level discreet ventilation. The attached spigot connects to the 110mm flexible hose, allowing the vent to be connected to soil vent pipes.

- Integral 110mm dia. spigot for connection to soil vent pipes
- Designed for use with natural or manufactured slate
- Fitted with integral insect grille and pre-drilled hole for fixings

Vent	Type of Roof
HP1/HP2	Slate
All vents are subjected to 3 separate wind and rain penetration tests and a deluge test to simulate extremely harsh weather, based on conditions developed as part of a DoE Partners in Technology Programme as used by Building Research Establishment (BRE). All vents exceed the pass criteria under all conditions.	

Product Specifications	HP1/HP2
Length	HP1 – 600mm, HP2 – 500mm
Width	HP1 – 300mm, HP2 – 250mm
Material	UV stabilised Polypropylene, with 110mm dia. PVC spigot
Colour	Blue/Black
Thickness	3mm
Flexi Hose Length	600mm (extended)



Product Requirements	
Statutory Requirements	To provide a means of ventilating a soil vent pipe in accordance with Building Regs Approved C2 & H1 and BS12056-2:2000.
Functional Requirements	The vent should give a proper fit to surrounding slates. The head and side laps must conform to the surrounding slates. Suitable for fixing in accordance with BS5534: Part 1:2014. Give minimum cutting of battens and surrounding slates, to provide a means of connection to 110mm dia. soil vent pipe.
Minimum Roof Pitch	20° degrees

