

Ref. Code: AP026

Date: April 2016



## FV25 Over Fascia Vent

### Product Description

Corovent over-fascia vents provide discreet eaves ventilation. The vents are strong and robust. They will resist the weight of tiles and slates, and also resist crushing by foot. The vents can be used on their own or in conjunction with other Corovent products.

- Provides continuous 25mm ventilation into the roof void
- Minimum disruption to eaves detail
- Simple to fix
- Corrosion and rot resistant
- For use with slate or tiled roofs



|                                |  |
|--------------------------------|--|
| <b>Product Requirements</b>    | <b>FV25</b>  |
| <b>Statutory Requirements</b>  | To provide ventilation at the eaves of a roof in accordance with Building Regs Document C2 & BS5250:2011 and The Building Standards (Scotland) Regulations. To achieve clear 25mm ventilation along the eaves (25,000mm <sup>2</sup> per metre)  |
| <b>Functional Requirements</b> | To fit properly on fascia and provide eaves ventilation. To be easily installed and be suitable for use with other Corovent products. To ensure a continuous 25mm ventilation gap is provided at the eaves. The 4mm slots prevent birds, large insects and vermin from entering the roof void. |

| Product Specifications   |               |
|--------------------------|---------------|
| Code                     | <b>FV25</b>   |
| Height                   | 32mm          |
| Width                    | 48mm          |
| Length                   | 1000mm ± 10mm |
| Material                 | HDPE          |
| Colour                   | Black         |
| Weight                   | 0.18Kg        |
| No. of Ventilation Slots | 168           |
| Vent Slot Width          | 4mm           |
| Vent Slot Depth          | 38mm          |

